

ZW350

Compact high brightness laser projector









- Bright WXGA DuraCore laser projector 3500 lumens and IP6X certified
- Easy installation 1.3x zoom, 360-degree and portrait projection
- Ultimate control Crestron, Extron, AMX, PJ-Link and Telnet LAN commands
- DuraCore laser technology 30,000 hours maintenance-free laser light source



The ZW350 is a compact WXGA DuraCore IP6X laser projector. Designed for maintenance-free continuous operation, it can be installed in virtually any orientation. Its small and lightweight footprint and 1.3x zoom combined with 360-degree and portrait projection make it easy to install.

This feature-packed projector has a built-in speaker and its laser technology delivers up to 30,000 hours of maintenance-free laser light source. For ultimate control, it comes with an RJ45 connection for monitoring and controlling a network across multiple rooms.

Specifications

Specifications	
Display/image	
Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness	3,500 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Has vertical auto keystone	Yes
correction	
Displayable colours (millions)	1073.4
Horizontal scan rate	15.375 ~ 91.146 Khz
Vertical scan rate	50 ~ 85 Hz (120Hz for 3D)Hz
Uniformity	75%
Screen size	0.76m ~ 7.65m (30.1" ~ 301") diagonal
Lamp info	Lease
Light source type LASER life	Laser 30,000 hours
	30,000 Hours
Optical Throw ratio	1.18:1 ~ 1.54:1
Throw ratio Projection distance (m)	1.16.1 ~ 1.34.1 1m - 7.7m
Zoom	1.3
Zoom type	Manual
Focal length (mm)	16.901 ~ 21.6076
Native offset	113%
Connectivity	11070
Connections	Inputs 2 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1
	x Audio 3.5mm
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x RS232, 1 x RJ45, 1 x micro USB service
General	
Noise level (typical)	30dB
Noise level (max)	32dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
	SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
	720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:
	1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian,
	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian,
	Chinese (simplified), Spanish, Swedish, Chinese (traditional),
	Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1 15W
Watts per speaker In the box	
In the box	AC power cord Remote control
	2x AAA batteries
	Basic user manual
Optional wireless models	UHDCast Pro
Networking	
	Yes
Networking	
Networking LAN - control	Yes 100V ~ 240V, 50-60Hz
Networking LAN - control Power	
Networking LAN - control Power Power supply Power consumption (standby) Power consumption (min)	100V ~ 240V, 50-60Hz <0.5W 138W
Networking LAN - control Power Power supply Power consumption (standby)	100V ~ 240V, 50-60Hz <0.5W
Networking LAN - control Power Power supply Power consumption (standby) Power consumption (min)	100V ~ 240V, 50-60Hz <0.5W 138W

6.2 kg

4 kg

Gross weight Net weight





